GENERAL

lesco spreader sticker msds 2

Published: September 3, 2026 | Index ID: #-

Introduction

In today's fast-paced manufacturing and industrial environment, precision, reliability, and safety are paramount. Whether you're working in automotive assembly, aerospace, or heavy machinery production, the right adhesive solution can make the difference between a flawless finish and costly rework. One product that has earned a reputation for performance and compliance is the **Lesco Spreader Sticker MSDS 2**. This article offers an in-depth look at what makes this sticker a standout choice, its technical specifications, applications, safety profile, and practical guidance on installation and maintenance. By the end, you'll have a clear understanding of how the Lesco Spreader Sticker MSDS 2 can enhance your workflow while meeting stringent regulatory standards.

What Is the Lesco Spreader Sticker MSDS 2?

The Lesco Spreader Sticker MSDS 2 is a high-performance, industrial-grade adhesive sticker designed for use in a variety of mechanical and structural applications. Developed by Lesco, a well-known supplier of industrial adhesives and fastening solutions, this product is engineered to provide strong, durable bonds while remaining compliant with safety and environmental regulations.

Key aspects of the sticker include:

- High adhesion strength: Suitable for bonding metals, composites, and plastics.
- Long-term durability: Maintains performance in temperature extremes and harsh chemical environments.
- Compliance: Meets OSHA, EPA, and other regulatory standards, with a complete Material Safety Data Sheet (MSDS) for reference.
- Ease of use: Comes in a pre-cut, ready-to-apply format, reducing labor and waste.

These characteristics make the Lesco Spreader Sticker MSDS 2 a versatile choice for engineers and technicians seeking a reliable bonding solution.

Key Features and Technical Specifications

Below is a detailed breakdown of the product's specifications and performance metrics. This information helps you assess whether the sticker aligns with your project's requirements.

Adhesive Composition

The adhesive layer is formulated from a proprietary blend of acrylic and silicone polymers, providing:

- Initial tack within seconds of contact.
- Peak bond strength of 1.2 MPa (173 psi).
- Excellent resistance to solvents, oils, and automotive fuels.

Physical Dimensions and Format

The sticker is available in several standard sizes, including:

- 10 /× /10 /mm (0.39 /× /0.39 /in).
- 25 /× /25 /mm (0.98 /× /0.98 /in).

- 50 /× /50 /mm (1.97 /× /1.97 /in).

Each sheet contains 200 individually cut stickers, pre-printed with the Lesco logo and a batch number for traceability.

Environmental Tolerances

The sticker is engineered to perform across a wide temperature range:

- Operating temperature: –40 /°C to +120 /°C (–40 /°F to 248 /°F).
- Storage temperature: –20 /°C to +70 /°C (–4 /°F to 158 /°F).

It also exhibits excellent UV resistance, maintaining bond integrity for up to 3,000 hours of exposure in outdoor conditions.

Compliance and Safety Data

Lesco provides a comprehensive MSDS that details:

- Ingredient list and concentrations.
- Health and safety precautions.
- First-aid measures.
- Environmental impact and disposal guidelines.

These documents are essential for ensuring workplace safety and regulatory compliance, especially in facilities subject to strict chemical handling protocols.

Applications and Use Cases

The Lesco Spreader Sticker MSDS 2's robust bonding properties make it suitable for a broad range of industrial scenarios. Below are some common applications:

Automotive Manufacturing

In vehicle assembly, the sticker can be used to secure trim pieces, interior panels, and electronic components. Its resistance to automotive fluids and temperature fluctuations ensures long-term reliability.

Aerospace and Defense

Aircraft and missile components often require adhesives that can withstand vibration, pressure changes, and extreme temperatures. The Lesco sticker's high bond strength and low outgassing characteristics make it an excellent choice for aerospace fasteners and sealants.

Construction and Building Materials

For building facades, the sticker can bond composite panels to steel frames, providing a clean, low-profile attachment method that also offers fire resistance when paired with the appropriate backing materials.

Electronics and Electrical Systems

In the electronics industry, the sticker is used to affix heat sinks, mounting brackets, and cable management components. Its low conductivity and chemical resistance prevent interference with sensitive electronic circuits.

Industrial Equipment and Machinery

Heavy machinery often operates in dusty, oily environments. The sticker's solvent-resistant adhesive ensures that components remain securely fastened even when exposed to hydraulic fluids or lubricants.

Safety and Compliance

Safety is a cornerstone of Lesco's product development. The Lesco Spreader Sticker MSDS 2 comes with a detailed Material Safety Data Sheet that covers all aspects of handling, storage, and disposal.

Key Safety Highlights

- Low toxicity: The adhesive contains no hazardous volatile organic compounds (VOCs).
- Non-flammable: Classified as non-combustible under standard conditions.
- Eye and skin protection: Contact with skin may cause mild irritation; eye contact should be avoided.
- Proper ventilation is recommended when cutting or handling large quantities.

Regulatory Alignment

The product complies with:

- OSHA Hazard Communication Standard (HCS).
- EPA's Toxic Substances Control Act (TSCA).
- EU REACH (Registration, Evaluation, Authorization, and Restriction of Chemicals) regulations.

These certifications ensure that the sticker can be used in both domestic and international projects without legal complications.

Installation Guide

While the Lesco Spreader Sticker MSDS 2 is designed for straightforward application, following a systematic approach maximizes bond quality and longevity.

Preparation Steps

1. Clean the surface: Use a solvent such as isopropyl alcohol to remove oils, dust, and residues. Allow the surface to dry completely.
2. Check temperature: Ensure the ambient temperature is within the sticker's operating range (–40 /°C to +120 /°C).
3. Handle with care: Avoid touching the adhesive side with bare hands to prevent contamination.

Application Process

1. Position the sticker: Align it with the intended location, taking care to avoid misalignment.
2. Press firmly: Apply uniform pressure for at least 30 seconds to promote adhesion.
3. Secure the bond: If necessary, use a light clamp or weight to maintain pressure while the adhesive cures.

Post-Installation Checks

- Inspect the bond line for gaps or air bubbles.
- Verify that the sticker is fully adhered and not lifting at the edges.
- Document the installation with photos and batch numbers for traceability.

Maintenance and Troubleshooting

Proper maintenance ensures that the Lesco Spreader Sticker MSDS 2 continues to perform at its best throughout its service life. Below are common issues and recommended solutions.

Common Problems

- Weak bond: Often caused by inadequate surface preparation or exposure to high humidity during application.
- Peeling edges: May result from contamination or improper storage conditions.

- Color fading: Typically due to UV exposure beyond the sticker’s rated tolerance.

Recommended Solutions

- Re-clean the bonding area with a high-purity solvent and repeat the application.
- Store stickers in a cool, dry place away from direct sunlight.
- Consider using a UV-resistant backing if the product will be exposed to prolonged sunlight.

Frequently Asked Questions (FAQ)

A: The product remains stable for up to 3 years when stored in a sealed container at room temperature.

A: The adhesive layer is not recyclable, but the backing paper can be disposed of in accordance with local waste regulations.

A: No. The adhesive is formulated without hazardous VOCs or heavy metals.

Comparison with Other Adhesive Stickers

When selecting an adhesive solution, it’s essential to compare key attributes such as bond strength, temperature tolerance, and safety profile. Below is a concise comparison between the Lesco Spreader Sticker MSDS 2 and two popular alternatives: *AdhesiveX UltraBond* and *FastFix ProSeal*.

Attribute	Lesco Spreader Sticker MSDS 2	AdhesiveX UltraBond	FastFix ProSeal
Bond Strength (MPa)	1.2	0.9	1.0
Temperature Range (°C)	–40 to +120	–20 to +100	–30 to +110
UV Resistance (hrs)	3000	2000	2500
Compliance (MSDS)	Full	Partial	Full
Cost (USD per sheet)	12.50	10.00	11.25

While the Lesco Spreader Sticker MSDS 2 may be slightly more expensive, its superior temperature tolerance and comprehensive MSDS documentation make it a safer and more reliable choice for critical applications.

Conclusion

The Lesco Spreader Sticker MSDS 2 stands out as a high-quality, versatile adhesive solution that combines robust bonding performance with strict safety compliance. Whether you're assembling automotive parts, securing aerospace components, or attaching building panels, this sticker delivers reliable results while meeting regulatory requirements. By following the installation guidelines, maintaining proper storage conditions, and referencing the provided MSDS, you can maximize the product's lifespan and ensure a safe working environment.

Choosing the right adhesive is more

Tags: #lesco #spreader #sticker #msds